

# Retractable Chemical Injection Quills **250 psi**



### **Features**

- SAF·T·FLO retractable injection quills are engineered for safety and reliability.
- These high quality injection quills are optimal insertion and extraction instructions.
   for injecting a chemical solution into a pressurized water main or process piping system.
   Water main or process pipe may require
- Retractable feature allows operators to safely remove and insert the injection quill, while under system pressure. Consult Saf-T-Flo for insertion and extraction instructions.
  - Water main or process pipe may require shutdown based on system pressure.



Please contact our Asia Pacific distributor:

**H20 Rx** 

Phone: 0409 784 236 <u>www.h2orx.com.au</u>

Email: info@h2orx.com.au PO Box 748, Lane Cove NSW 1595



## **Retractable Chemical Injection Quills** 250 psi



Main Connection Size	Material of Construction	Solution Tube Diameter	Max. Length	Check Valve Available	Saf-T-Seal Tip Available	Base Model Number
3/4" NPT	SS	3/8"	6"	Optional	Yes	EB-168
1" NPT	SS	1/2"	6"	Optional	Yes	EB-155
1-1/4" NPT	SS	3/4"	8"	Optional	n/a	EB-147
1-1/2" NPT	SS	1"	10"	Optional	n/a	EB-148
2" NPT	SS	1-1/2"	12"	Optional	n/a	EB-150
2-1/2" NPT	SS	2"	12"	Optional	n/a	EB-153
3" NPT	SS	2-1/2"	12"	Optional	n/a	EB-151

#### **Features**

- Stainless Steel Ball Valve
- Dual Bolt Saf-T-Lock Restraint System
   Preset Welded Steel Limit Chains
- Tip Configuration
  - 1. Plain Tip
  - 2. Bevel Tip with Alignment Arrow
  - 3. SAF-T-SEAL
- Diffuser (Optional)
- Check Valve (Optional)

#### **Maintenance**

- Periodically remove solution tube to check for internal or exterior chemical build-up
- Apply grease to the compression o-ring
- Re-apply Anti-Seize to Adapter/Packing Nut threads

#### **Other Saf-T-Flo Models**

- 150 psi rated Retractable Injection Quills
- ALL PVC Retractable Injection Quills
- Non-Retractable Injection Quills
- Retractable Flanged Injectors
- Sampling Probes

Please contact our Asia Pacific distributor:



ABN: 97 217 924 685

Phone: 0409 784 236 www.h2orx.com.au

PO Box 748, Lane Cove NSW 1595 Email: info@h2orx.com.au

<sup>\*</sup> Max length is for PVC or CPVC solution tubes
\*\* Consult Saf-T-Flo when using a PVC or CPVC solution tube
Standard unit includes; SS ball valve, solution tube with plain tip, dual bolt Saf-T-Lock restraint system, and dual welded